



# DL-473 Biometric Terminal

The Viridi DL-473 biometric door lock is ideal for installation in residential or office environments with easy adaptation to most types of mechanical lock or 6VDC pre-existing system.

Purchase Code: 500.333

## • Features

The Viridi DL-473 biometric door lock brings safety, convenience and value to your environment. This unit is ideal for installation in residential or business, with easy adaptation to a 6V electric lock.

Functions: Low battery alert and a built-in thermal sensor that unlocks automatically in case of fire. Also, no interference from static electricity or electrical shock.

The Viridi DL-473 has an integrated 125 kHz RFID reader and biometrics for authentication. It is possible to manage and visualize the user through the USB interface with Management software.

## • Technical specifications

Built-in lock	No
Door Thickness	35 to 55 mm (standard) / Adjustable
Compatible locks	6V electric lock
Battery Power	4 AA alkaline batteries 1.5 V with a duration of approx. 7 months (20 times per day)
Number of Users	100 users
RF Card Capacity	50
Communication	USB
Operating Environment	-20 to 50 C° / RH <90% (not condensed)
Compliance standards	IPX3, CE / FCC (in progress)
Sensor type	500 dpi optical resolution
Time for identification (1:N)	< 1 sec
Authentication modes	Biometrics or RFID card 125 kHz (EM4100)
FRR / FAR	0,1% / 0,0001%
Material	Outside: Cast Aluminum Matrix Inside: ABS Battery cover: ABS
Dimensions	Outside: 59 x 124 x 38 mm Inside: 84 x 147 x 44 mm
Events capacity	4000
Reading distance	To 50 mm